



TACO - HIGH EFFICIENCY ECM PRODUCTS

POTABLE MODELS

CONTRACTORS: Contact your local Wholesaler for Pricing and Availability

RESIDENTIAL / LIGHT COMMERCIAL

MODEL/VENDOR #	DESCRIPTION	CONN	F/F	HP	ELECTRICAL	MAX SHUT-OFF HEAD	MAX FLOW	WT
006e3 VM1212-DY1-UP2A00	Composite HW Circulator: Infinitely Variable Speed *	1" union	5-1/8"	1/40	120V/1 PH	13 FT	11 GPM	4
006e3LC VM1212-DY1-UP2A01	Composite HW Circulator: Infinitely Variable Speed with 6' power cord *	1" union	5-1/8"	1/40	120V/1 PH	13 FT	11 GPM	4
007e-SF4 VB1016-DY2-4S2W00	SS Circulator: ECM, HI-Eff, V-Spd, 4 Bolt, Flanged <i>Available: September 2021</i>	Universal	6-3/8"	1/25	120V/1 PH	10 FT	16 GPM	6
007e-SU VB1016-DY2-US2W00	SS Circulator: ECM, HI-Eff, V-Spd, 4 Bolt, Flanged <i>Available: September 2021</i>	Union	6-3/8"	1/25	120V/1 PH	10 FT	16 GPM	6
0015e3-SF4 VM1816-DY2-4S2W00	SS Circulator: ECM, HI-Eff, V-Spd, 4 Bolt, Flanged <i>Available: September 2021</i>	Universal	6-3/8"	1/25	120V/1 PH	18 FT	16 GPM	6
0015e3-SU VM1816-DY2-US2W00	SS Circulator: ECM, HI-Eff, V-Spd, 4 Bolt, Flanged <i>Available: September 2021</i>	Union	6-3/8"	1/25	120V/1 PH	18 FT	16 GPM	6
0018e-SF4 VR1816-DY2-4S2W00	SS Circulator: ECM, HI-Eff, V-Spd, 4 Bolt, Flanged, Bluetooth <i>Available September 2021</i>	 Universal	6-3/8"	1/25	120V/1 PH	18 FT	16 GPM	6
0018e-SU VR1816-DY2-US2W00	SS Circulator: ECM, HI-Eff, V-Spd, 4 Bolt Flanged, Bluetooth <i>Available September 2021</i>	 Union	6-3/8"	1/25	120V/1 PH	18 FT	16 GPM	6
HLPe-1	Hot-LinkPlus-e (006e3 Circulator, Smart Plug Control, Hot Link Valve) Includes 3/4" NPT male & female union fitting set and (2) 1/2" x 1/2" SS flex hoses. **	3/4" NPT male x female	5-1/8"	1/40	120V/1 PH	13 FT	11 GPM	7
SPe-1	SmartPlus-e Hot Water Recirc System with Smart-Plug Control - composite construction, union connection (No IFC) *	1" union	5-1/8"	1/40	120V/1 PH	13 FT	11 GPM	5

*1/2" or 3/4" Sweat, NPT, Press fitting sets needed - sold separately.

** Sweat or Press 1/2" & 3/4" fitting sets available - sold separately.

FITTING SETS for 006e3, 006e3LC, and SmartPlus-e (SPe-1)

MODEL/VENDOR #	DESCRIPTION	INCLUDED IN EACH SET
UFS-050S	Fitting Set - 1/2" Union SWEAT	(2) gaskets, (2) union nuts, and (2) tail pieces.
UFS-050P	Fitting Set - 1/2" Union PRESS	(2) gaskets, (2) union nuts, and (2) tail pieces.
UFS-050T	Fitting Set - 1/2" Union FNPT	(2) gaskets, (2) union nuts, and (2) tail pieces.
UFS-075S	Fitting Set - 3/4" Union SWEAT	(2) gaskets, (2) union nuts, and (2) tail pieces.
UFS-075P	Fitting Set - 3/4" Union PRESS	(2) gaskets, (2) union nuts, and (2) tail pieces.
UFS-075T	Fitting Set - 3/4" Union FNPT	(2) gaskets, (2) union nuts, and (2) tail pieces.


LIGHT COMMERCIAL / COMMERCIAL

MODEL/VENDOR #	DESCRIPTION	CONN	F/F	HP	ELECTRICAL	MAX SHUT-OFF HEAD	MAX FLOW	WT
0026e-SF2 VM2644-DD1-RS2A00	SS Circulator: High-performance, Variable Speed, wet-rotor	Flanged Rotated	7"	1/6	115/208/230V 1PH	26 FT	44 GPM	11
0034e-SF2 VM3450-HY1-FS2A00	SS Circulator: High-performance, Variable Speed, wet-rotor, analog	Flanged Rotated	7"	1/4	115/208/230V 1PH	34 FT	50 GPM	11
0034eP-SF2 VR3450-HY1-FS2A00	SS Circulator: High-performance, Variable Speed, wet-rotor, intuitive digital user interface	Flanged Rotated	7"	1/4	115/208/230V 1PH	34 FT	50 GPM	11
1915e-SF VR65120-CB1-FS2A00	SS In-Line Pump: Self-Sensing, Close Coupled, Mechanically Sealed, 2 Bolt	Flanged 1-1/2"	10.4"	3/4	200/240V 1 PH	65 FT	120 GPM	30.5

TACO - HIGH EFFICIENCY ECM PRODUCTS

HYDRONIC MODELS

CONTRACTORS: Contact your local Wholesaler for Pricing and Availability

MODEL & VENDOR #	DESCRIPTION	CONN	F/F	HP	ELECTRICAL	MAX SHUT-OFF HEAD	MAX FLOW	WT
007e-2F4 VB1016-HY2-4C2A00	CI Circulator: Variable Speed, 4 Bolt	Flanged Universal	6-3/8"	1/25	120V/1 PH	10 FT	16 GPM	6
0015e3-2F4 VM1816-HY2-4C2A00	CI Circulator: Variable Speed, 4 Bolt	Flanged Universal	6-3/8"	1/25	120V/1 PH	18 FT	16 GPM	6
0018e-2F4 VR1816-HY2-4C2A01	CI Circulator: Variable Speed, 4 Bolt, Bluetooth	 Flanged Universal	6-3/8"	1/25	120V/1 PH	18 FT	16 GPM	6
0026e-F2 VM2644-HD1-RC2A00	CI Circulator: High-performance, Variable Speed, wet-rotor	Flanged Rotated	7"	1/6	115/208/230V 1PH	26 FT	44 GPM	11
0034e-F2 VM3450-HY1-FC2A00	CI Circulator: High-performance, Variable Speed, wet-rotor, analog	Flanged Rotated	7"	1/4	115/208/230V 1PH	34 FT	50 GPM	11
0034eP-F2 VR3450-HY1-FC2A00	CI Circulator: High-performance, Variable Speed, wet-rotor, intuitive digital user interface	Flanged Rotated	7"	1/4	115/208/230V 1PH	34 FT	50 GPM	11
VR1816-HY2-4C2A00	CI Circulator: Infinitely Variable Speed, 4 Bolt	Flanged Universal	6-3/8"	1/25	120V/1 PH	18 FT	16 GPM	6
VT2218-HY2-4C1A00	CI Circulator: Delta-T, Variable Speed, 4 Bolt	Flanged Universal	6-3/8"	1/25	110-120V 1 PH	22 FT	18 GPM	8
1915e-F VR65120-HB1-FC2A00	CI In-Line Pump: Self-Sensing, Close Coupled, Mechanically Sealed, 2 Bolt	Flanged 1-1/2"	10.4"	3/4	200/240V 1 PH	65 FT	120 GPM	31
VR15-3	Circulator: CI Casing with SS Impeller, Variable Speed, Canned Wet-Rotor	ANSI Flange 1-1/2"	9-13/16"	0.68	110-240V 1 PH	40 FT	120 GPM	57
VR20-3	Circulator: CI Casing with SS Impeller, Variable Speed, Canned Wet-Rotor	ANSI Flange 2"	11"	1.088	110-240V 1 PH	41 FT	200 GPM	71
VR25-3	Circulator: CI Casing with SS Impeller, Variable Speed, Canned Wet-Rotor	ANSI Flange 2-1/2"	13-3/8"	1.496	230-240V 1 PH	42 FT	300 GPM	82
VR30-3	Circulator: CI Casing with SS Impeller, Variable Speed, Canned Wet-Rotor	ANSI Flange 3"	14-3/16"	2.175	230-240V 1 PH	38 FT	360 GPM	99

TACO MODEL REPLACEMENT CHARTS

Charts are for quick reference only. Review the duty point on the pump curve for an accurate cross reference.

Note: Flange size and flange-to-flange dimensions will vary by competitive model and may require some piping changes.



0018e Bluetooth (6-3/8" F/F dimension) Replaces:			
TACO	GRUNDFOS	XYLEM / B & G	ARMSTRONG
005	ALPHA 15-55F	ecocirc 19-14 auto	Astro 20
006	ALPHA 15-55FR	ecocirc 19-14 vario	Astro 25
007	UP 15-10F	NRF-9F/LW	Astro 30
008	UP 15-10FR	NRF-22	Astro 30-3
0015 (3 spd)	UP 15-42F	NRF-25	Astro 50-3
00R	UP 15-42FR		Astro 230CI
00R (3 spd)	UPS 15-42F		Astro 230CI-R
	UPS 15-58FC		Astro 250CI
	UPS 15-58FRC		Astro 250CI-R
			Compass 20-20

0026e Replaces:			
TACO	BELL & GOSSETT	ARMSTRONG	GRUNDFOS
0010	NRF 36	Astro 280	Magna 32-60
0011	ecocirc XL 20-35	Astro 210	Alpha2 26-99
0012	ecocirc XL 36-45	Compass ECM	
0014			
110	Series HV	S 25	UP 26-96
111	Series PR	H 52	UP 26-64
112	Series HV	H 52	UPS 32-40
113	Series 100	H 32	UPS 32-80
2400-10	PL50	E 13	UP 50-75
2400-20	PL30	E 11	UPS 50-44
2400-30	Series e (e-601)	E 10	UP 43-75
2400-40	Series 60 (601)	E 7	UP(S) 26-99

007e (6-3/8" F/F dimension) Replaces:		
TACO	GRUNDFOS	XYLEM / B & G
007	ALPHA 15-55F	ecocirc 19-14 auto
	UPS 15-42	ecocirc 19-14 vario
	UPS 15-58	NRF-22
		NRF-25

0015e3 (6-3/8" F/F dimension) Replaces:		
TACO	GRUNDFOS	XYLEM / B & G
005	UP 15-10F	ecocirc 19-14 auto
006	UP 15-10FR	ecocirc 19-14 vario
007	UP 15-42F	NRF-9F/LW
008	UP 15-42FR	NRF-22
0015 (3 spd)	UPS 15-42F	NRF-25
00R	UPS 15-58FC	
00R (3 spd)	UPS 15-58FRC	
	ALPHA 15-55F	
	ALPHA 15-55FR	

0034e Replaces:			
TACO	BELL & GOSSETT	ARMSTRONG	GRUNDFOS
009	E90 1AAB	1050 1B	Alpha 26-99
0010	ecocirc XL 36-45	1050 1B 1/4B	Magna 32-60
0011	NRF-36	Astro 210	Magna 32-100
0012	NRF-45	Astro 280	TP(3) 32-40
0013	PL 30	Astro 290	UP 26-64
0014	PL 36	Compass ECM	UP 26-96
110	PL 45	E 10	UP 26-116
111	PL 50	E 11	UP 43-75
112	Series 60 (601)	E 7	UP 50-75
113	Series 100	E 8	UPS 26-99
2400-10	Series HV	H 51	UPS 32-40
2400-20	Series PR	H 52	UPS-32-80
2400-30		H 63	UPS 43-44
2400-40		S 25	UPS 43-100
VR3452			UPS 50-44

Washington & Oregon
FOR ASSISTANCE CONTACT:
Corby Olsen:
(503) 476-6879 - colsen@GoPSi.com
Nick Hollobon:
(206) 643-4874 - nhollobon@GoPSi.com
Owen Phillips:
(206) 954-0638 - ophillips@GoPSi.com

